


Vinyl Coated Polyester Swatch Card



18 OZ ROYAL BLUE SHOWN

Stock Colors



BLACK



BROWN



GREY



WHITE



TAN/BEIGE



FOREST GREEN

Premium Colors



ORANGE



RED



YELLOW



PURPLE



GREEN



LIGHT BLUE



NAVY BLUE



ROYAL BLUE

COLOR AVAILABILITY MAY VARY BY WEIGHT.
ACTUAL COLORS MAY VARY FROM THOSE PRINTED.
PLEASE CONSULT YOUR SALES REPRESENTATIVE.

PRODUCT SPECIFICATIONS

PVC COATED POLYESTER FABRIC

MATERIAL DESCRIPTION					
MATERIAL	10 OZ	14 OZ	18 OZ	22 OZ	40 OZ
MATERIAL WEIGHT (OZ/YD ²)	10	14	18	22	40
ROLL WIDTH (IN)	61	61	61	61	61
ROLL LENGTH (YD)	100	100	100	100	50
NET WEIGHT (LBS)	106	148	196	233	212
BASE FABRIC FIBER	Woven Polyester	Woven Polyester	Woven Polyester	Woven Polyester	Woven Polyester
YARD (DENIER)	1000 X 1000	1000 X 1000	1000 X 1300	1300 X 1300	1300 X 1300
FABRIC COUNT (THREADS/SQ IN)	20 X 20	16 X 16	18 X 17	18 X 17	30 X 30
TYPE OF COATING	PVC	PVC	PVC	PVC	PVC

MATERIAL DESCRIPTION											
ROLL DIMENSIONS		10 OZ		14 OZ		18 OZ		22 OZ		40 OZ	
		VALUE	ASTM STD	VALUE	ASTM STD	VALUE	ASTM STD	VALUE	ASTM STD	VALUE	ASTM STD
TENSILE STRENGTH (LBS/2 IN)	WARP	492	D5035	420	D5035	480	D5035	640	D5035	460	D751
	WEFT	450		375		500		595		416	
TEAR STRENGTH (LBS)	WARP	60	D2261	50	D2261	90	D2261	100	D2261	120	D751
	WEFT	55		40		70		85		108	
ADHESION STRENGTH (LBS/2 IN)		15	D2724	20	D2724	18	D2724	17.5	D 2724	14	D751
TEMPERATURE RESISTANCE (°F)		-20° ~ 150°		-20° ~ 150°		-20° ~ 150°		-20° ~ 150°		-20° ~ 150°	
UV		For Exterior Applications		For Exterior Applications		For Exterior Applications		For Exterior Applications		For Exterior Applications	

Note: The technical specifications contained herein are believed to be reliable, but no representations, guarantees or warranties of any kind are made regarding their accuracy or suitability of the material for particular applications.



info@enclosureguy.com • Phone Toll Free 888.254.6892
1507 N. Saint Joseph St. • Gonzales, TX 78629

Enclosure Guy is a registered trademark of Landmark A&E, LLC